

Glitel GT-318RI

ADSL Router



Specification

Glitel GT-318RI is an ADSL router in a simple design with a pleasant look and relatively small size. 1 LAN port 10 / 100Mbps allows user to connect a computer or even multiple computers through a switch, hub or WiFi router. Glitel GT-318RI provides to user a stable support for browsing the Internet, watching videos or playing online games. Very reliable and durable solution of Glitel GT-318RI is suitable for homes and small businesses.

Functions and features

- 1x RJ45 LAN port 10/100Mbps
- 1x DSL port
- Pleasant look and relatively small size
- Bridge function
- Web interface in Slovak language

Parametres

- LAN ports: one 10/100 Mbps LAN port
- Standards: ANSI T1.413 issue 2
G.992.5 (ADSL2+)
ITU-T G.992.1 (G.dmt), G.992.2 (G.lite) Annex B
ITU-T G.992.3 (ADSL2 DMT), G.992.4 (ADSL2 G.lite)
RFC2684 Bridge and Routed LLC& VC
RFC2364 PPP through ATM ALL5
RFC2516 PPP through Ethernet
RFC2225/RFC1577 classic IP through ATM
Transparent Bridge
ATM Forum UNI 3.1/4.0 PVC
F5 OAM Loopback / Send and Receive
- Support: Downstream to 24 Mbps
Upstream to 1 Mbps
Static and dynamic routing
IP/TCP/UDP/ICMP/ARP/RARP
NAT
Ports mapping/forwarding
DHCP Server/Relay/client
DMZ
DNS Relay Agent
SNMP V1.0
UBR, CBR, GFR and VBR services
PPP always on with configurable timeout
PPP Dial on Demand
- Security: PAP/CHAP autentification for PPP mode
NAT
SPI for firewall with Denial-of-Service (DoS) protection
ALG (Application-level gateway) for NAT/PAT support
2-level (User/Admin) router interface
- Size: 152mm x 115mm x 40mm

Package

- 1x ADSL Router Glitel GT-318RI
- 1x Power adapter
- 1x RJ11 Telephone line cable
- 1x RJ45 Ethernet cable
- 1x xDSL splitter
- 1x User manual